

FABRIC WATER-BASED CONCENTRATE

DESCRIPTION AND USES

Rust-Oleum® NeverWet® Water-Based Concentrate is a one-step, superhydrophobic, water-repelling treatment designed to keep textiles dry. This crystal clear formula allows fabrics to breathe, while repelling water from the surface. NeverWet Fabric Water-Based Concentrate preserves fabric from damaging moisture without changing the look or feel of the fabric.

NeverWet Fabric Water-Based Concentrate is ideal for use on polyester, nylon, suede and more. It is applied in the water bath stage in textile mills.

PRODUCTS

SKU	Description	
284292	1-Gallon	_
284291	5-Gallon	
284301	55-Gallon	

PRODUCT APPLICATION

MILL APPLICATION

NeverWet Fabric Water-Based Concentrate should be incorporated at a ratio of 30:1 (Mill Material to Concentrate). Run a small amount of material, and once it has dried, test for desired performance characteristics. If higher performance for stain repellency or water repellency is desired, the ratio may be adjusted to 20:1. Treated fabrics may be cured at ambient temperature (70°F) for 24 hours, but best performance for stain repellency, water repellency, and dry time is achieved by curing textiles at elevated temperatures: 300-360°F for 4-6 minutes depending on fabric type.

PHYSICAL PROPERTIES

Physical Pro	operties	FABRIC WATER-BASED CONCENTRATE	
Resin		Acrylic	
Solvents		Water	
Weight	Per Gallon	9.10 lbs.	
	Per Liter	1.09 kg	
Solids	By Weight	30.0%	
	By Volume	23.7%	
Volatile Organic Compounds		0 g/l	
Shelf Life		2 years	
Flash Point		>200°F (93°C)	
Safety Infor	mation	For additional information, see MSDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 877•385•8155 www.rustoleum.com/industrial Form: GDH-485 Rev.: 072015