

型号 Type		JSD2000	JSD508
箝幅 (cm) Reed width		130,150,170,190,210,230,260,280,300,320,350,360(cm)	
有效幅宽 (cm) Valid fabric width		最大宽幅=箝幅-2CM, 最小宽幅=箝幅-50CM Nominal R/S minus 2cm to 50 cm	
构造 Frame		箱体式结构 (主要采用油池润滑) Box frame type driving section is an oil bath	
传动部分 Driving	刹车 Brake	机电一体化, 电磁离合器控制机械式刹车 Direct stop mechanism by an electromagnetic brike	
	控制 Control	按钮式和触摸式, 开关键, 准备键, 正转键, 逆转键, 停止键 Push and touch button, ready, run, stop, forward inching, reverse inching, one step reverse	
	主电机 Motor	带超起动功能, 可连续运转电机 Rush start motor	
	电机功率 Motor capacity	1.5KW, 1.8KW, 2.2KW, 2.4KW, 5.6KW, 2.8KW, 3.0KW, 3.7KW, 4.5KW, 5.4KW	
打纬机构 Beating		曲柄系统 Crank beating	
送经机构 Let off	构造 System	全自动机械连续送经或电子式连续送经, 单经轴或垂直式双经轴。 Automatic mechanical or electronic continuous let-off, one roll or two vertical roll	
	经轴直径 Warp beam diameter	800MM 法兰盘, 178MM 筒管 800MM Flange, 178MM barrel	
卷曲机构 Take-up	构造 System	机械连续卷曲或电子式连续卷曲 Mechanical or electronic continuous take-up	
	适用纬密 Pick weft density	常规: 5-60 纬/cm, 特定: 4-100 纬/cm Normal: 5-60 pick/cm, Special:4-100 pick/cm	
	布匹卷曲直径 Cloth wind-up	420mm, 520mm,600mm	

	diameter	
引纬机构 Weft insertion	测长机构 Measuring	300 型 RDP 风机式机械测长（单喷）或电子储纬式测长（1-6 喷） 300RDP type mechanical measuring turbo blower (single nozzle) or electric weft feeder(1-6 nozzles)
	泵体 Pump	M 型, L 型, H 型, 单个或双个 Type :M, L, H, single or double
	水泵柱塞 Pump piston	32/17,32/18,32/20,36/22,36/24,36/26,39/26,39/28,39/30,50/35 ceramic piston
	喷针 Nozzle needle	ST20/10, ST30/10, ST45/20, ST750/40
	喷咀个数 Weft filling	1 个喷咀, 2 个喷咀, 3 个喷咀, 4 个喷咀, 6 个喷咀 1,2,3,4,6 nozzle
	探纬 Filling feeler	电子自控式光电探纬 Electronic, optical and self-control
耳丝部分 Selvage		恒星、行星齿轮式运动, 交叉捻入系统 Twisting by star and planetary gears
电器部分 Electrical part	国产 进口 Domestic and import	主控板, 交流接触器, 变压器, 数据借口, 耳丝断自停装置, 废丝断自停装置, 过载过热保护。 Main control board, AC contactor, transformer, NC interface, selvage break system, waste yarn break system, overheating and overload protection.
	电子码表 Electronic meter	织机转速、总产量、分班产量、总效率、分班效率、定布长度自动控制, 停机原因汇总并显示 Count and display, rotation speed, total yield, tem yield, total efficiency, stopping analysis and display, cloth length auto control, stopping , analysis and disply.
随机配送 Other devices		卷布辊一根, 纬密齿轮一个, 废丝筒一个, 喷针一套 A cloth roller, a weft density gear, a trashcan, a set of neezle
开口机构	平织 Plain shedding	曲柄开口 (2-8 片), 平纹组织 Crank shedding(heald frame number:2-8), 1/1 fabric

Shedding	凸轮 Cam shedding	凸轮开口部（2-14 片），平纹、斜纹、缎纹组织 Cam shedding (2-14 heald frame), plain, twill, satin fabric
	多臂 Dobby	消、积极式（最多 16 片综框），电子或机械式读取机构，平 纹、斜纹、缎纹，变化组织 Positive/negative at most 16 heald frame, electronic and mechanical system, plain, twill, satin or complex design
	提花 Jacquard	1408,2688,5129 lifting hooks, electronic jacquard device